



Illustrative picture

SPECIFICS

Description	Product type	MULTIPRESA INDUSTRIALE
	Article code	2301MT
	Commercial Series	/

General Data	Poles	N° 3	Type of material	ABS						
	Current	A 16	Dimensional stability	°C -25 /+70						
	Voltage	V~ 230	Resistance glow wire test	°C +650 / +850						
	Power	kW 3	Working temperature	°C , -25 + 40						
	Degree of protection	IP 44	Weight	kg 3,7						
	Impact Resistance	IK 08	Portable	Yes						
	Insulation Resistance	MΩ >10	Emergency push button	No						
			Connection	Plug						
		Behaviour with chemical and atmospheric agents								
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant 	Limited Resistant 	Resistant 	Resistant 	Resistant 	Limited Resistant 	Limited Resistant 	Resistant 	Resistant 	Resistant 	Resistant 

Standards	CEI EN 61439-3	2014/35/UE
-----------	----------------	------------

Features package	Descriptions		N/pieces	Weight/kg
	Article	/	/	/
	Package innerbox	/	/	/
	Packaging	/	/	/

Description	Composition of the Multi-socket	
	3 Pr. 16A-6h 2P+E IP44 200-250V~	
	1 Sp. 16A-6h 2P+E IP44 200-250V~	
	1 Automatic switch, MT 2P 16A 6kA C	



Reg. A.E.E n° IT17100000010057

DATA	RESPONSABILE TECNICO
15/06/2021	Romano Rosi